



VF-560 〈0~1MHz〉	VF-565 〈5MHz〉	VF-570 〈10MHz〉
0~10 V 0~700 μ A 15 K Ω ± 5 mV max 20 μ V/ $^{\circ}$ C max 10 %	0~10 V 0~1.7 mA 5.6 K Ω ± 5 mV max 20 μ V/ $^{\circ}$ C max 10 %	0~10 V 0~1.7 mA 5.6 K Ω ± 5 mV max 20 μ V/ $^{\circ}$ C max 10 %
$F_o = K \cdot (V_{in} - V_{os}) / (R_i + 15) \text{ K}\Omega$ $F_o = K \cdot \ln$ 但 $K \div 1.6 \text{ KHz}/\mu\text{A}$ 0~1 MHz TTL コンパチブル  500 Ω 以下	$F_o = K \cdot (V_{in} - V_{os}) / (R_i + 5.8) \text{ K}\Omega$ $F_o = K \cdot \ln$ 但 $K \div 3 \text{ KHz}/\mu\text{A}$ 0~5 MHz TTL コンパチブル  15 Ω 以下	$F_o = K \cdot (V_{in} - V_{os}) / (R_i + 5.6) \text{ K}\Omega$ $F_o = K \cdot \ln$ 但 $K \div 6 \text{ KHz}/\mu\text{A}$ 0~10 MHz TTL コンパチブル  150 Ω 以下
0.01 % typ、0.05 % max	0.01 % typ、0.05 % max	0.01 % typ、0.05 % max
100 μ V 500 PA	10 μ V 100 PA	10 μ V 100 PA
20ppm/ $^{\circ}$ C typ、50ppm/ $^{\circ}$ C max 500 ppm/month max 100 ppm/ $\pm$ V max 20 K Ω トリマー	20ppm/ $^{\circ}$ C typ、50ppm/ $^{\circ}$ C max 500 ppm/month max 100 ppm/ $\pm$ V max 20 K Ω トリマー	50ppm/ $^{\circ}$ C typ、100ppm/ $^{\circ}$ C max 500 ppm/month max 100 ppm/ $\pm$ V max 20 K Ω トリマー
1 μ s + 1 puls	1 μ sec + 1 puls	500 nS + 1 puls
± 15 V、 ± 18 mA ± 14 V~16 V	± 15 V、 ± 14 mA ± 25 mA ± 14 V~16 V	± 15 V、 ± 14 mA ± 35 mA ± 14 V~16 V
0~+60 $^{\circ}$ C -25~+85 $^{\circ}$ C -55~+125 $^{\circ}$ C	0~+60 $^{\circ}$ C -25~+85 $^{\circ}$ C -55~+125 $^{\circ}$ C	0~+60 $^{\circ}$ C -25~+85 $^{\circ}$ C -55~+125 $^{\circ}$ C
AMS4L	AMS4L	AMS4L



VF-560・VF-565・VF-570

